

Aurubis Bulgaria AD, BG - 2070 Pirdop

Aurubis Bulgaria AD
Industrial zone
BG - 2070 Pirdop
Tel: +359 728 62-303
Fax: +359 728 62-636
info.pirdop@aurubis.com
www.aurubis.com

DECLARATION OF PERFORMANCE No 3C/1871 - CPR - 0372/02.10.2024

- 1. Unique product type identification code:
 iron silicate fines
- 2. Type, batch or serial number or other element that allows product identification in accordance with Article 11, Para 4 of Regulation (EU) No 305/2011:

manufactured filler aggregate

- 3. Intended use of the construction product in accordance with the applicable harmonized technical specification: for concrete production in buildings, roads and other civil engineering works in accordance with EN 12620:2002+A1:2008
- 4. Name, registered trade name and contact address pursuant to Article 11 Para 5 of Regulation (EU) No 305/2011: Aurubis Bulgaria AD, Industrial zone, 2070 Pirdop
- 5. If applicable, name and contact address of authorized representative, whose power of attorney includes the tasks in Article 12, Para 2 of Regulation (EU) No 305/2011:

 not applicable
- 6. System for assessment and verification of constancy of performance of the construction product as set out in Regulation (EU) No 305/2011, Annex V: system 2+
- 7. In the case of performance concerning a construction product covered by a harmonized standard:
 "Center for testing and European certification" LTD, Notified certification body with identification number NB 1871 by the register of the European commission, assess initial control of the production and the production control, observe permanent monitoring, assessment and approval of the production control in accordance with system 2+ and publish Certificate of conformity of the factory production control 1871 CPR 0372.
- 8. In the case of declaration of performance of construction product, which has already a European Technical Assessment: not applicable



9. Declared performance characteristics:

Main characteristics	Declared performance characteristics	Harmonized technical specification
Fine fraction, size and density of the grains	Fine filler Grain size distribution - Percent passing through sieve with openings: 2 mm 100 % 0,125 mm 85 до 100 % 0,063 mm 70 до 100 %	
	Density of the grains: $3.6 \div M \ 3.9 \ Mg/m^3$ Water absorption: $\leq 0.1 \ %$	2008
Composition/	Chlorides: ≤ 0,01 %	•••
content	Acid soluble sulfates: AS 0,8	:+A1
	Total sulfur content: < 1%	002
3 · · · · · · · · · · · · · · · · · · ·	Components, which change setting time and hardening time of concrete: - content of organic impurities - humous content: not detected	r 12620:2002+A1
Purity	Content of fine fraction: in accordance with the requirements by EN 12620:2002+A1:2008, table 7	B
Durability	Alkali-silica reaction* - content of soluble SiO ₂ : < 50 mmol/dm ³ - relative linear elongation of cement	
Dangerous substance	Content of natural radionuclides Index of specific activity*: I < 1	

^{*}Requirement by the national regulations

10. The performance of the product identified in items 1 and 2 corresponds to the declared characteristics in paragraph 9.

This declaration of performance is issued entirely under responsibility of the manufacturer referred to in Para4.

Signed for and on behalf of the manufacturer by: eng. Emanuela Manolova, PhD., Iron silicate business development manager

Place and date of issue: Pirdop, 02.10.2024

2/3





1871

"AURUBIS BULGARIA" AD

Industrial zone, 2070 Pirdop

22

3C/1871-CPD-0372

EN 12620:2002+A1:2008

Manufactured aggregate

for production of concrete for buildings, roads and other civil engineering works

Fine fraction, size and density of the grains

Fine filler

Grain size distribution -

percent passing through sieve:

2 mm

100 %

0,125 mm 85 to 100 %

0,063 mm 70 to 100 %

Density of the grains: $3,6 \div 3,9 \text{ Mg/m}^3$

Water absorption: ≤ 0,1 %

Composition/content

Chloride content: ≤ 0,01 %

Content of acid-soluble sulfates: AS 0.8

Total sulfur content, presented by SO_3 : < 1% Content of organic impurities: not detected

Humus content: not detected

Durability

Alkali-silica reaction*

- content of soluble SiO_2 : < 50 mmol/dm³

Dangerous substances

Content of natural radionuclides
Index of specific activity*: I < 1

*Requirement by the national regulations